## CHRYSLER 62TE TRANSMISSION

**APPLICATIONS** 

Chrysler: 200, Pacifica, Sebring, Town & Country Dodge: Avenger, Grand Caravan, Journey Ram: C/V, Promaster Volkswagen: Routan

Since 1942





## SCAN OUR QR CODE

SCAN THIS OR CODE TO VIEW JASPER'S CHRYSLER 62TE VIDEO LIBRARY.



C

JASPER prevents loss of 3rd and 6th gear by installing an improved snap ring in the case. JASPER's snap ring is 27% greater in radial thickness which significantly increases the retaining force, ensuring the snap ring remains engaged.

🔊 f 🔰 🛗 🧿

JASPER prevents hydraulic leaks between the Underdrive, Overdrive, and Reverse clutch by installing solid PTFE stator support seals. PTFE seals are superior to OE steel seals in separating these hydraulic circuits.

800-827-7455 • WWW.JASPERENGINES.COM



JASPER prevents hydraulic leaks by installing solid PTFE stator support seals.


JASPER installs a billet front cover on each Chrysler 62TE. Billet front covers are machined from a solid piece of steel. This is an improvement over the original stamped design that is prone to distortion and cracking.

Each converter is dynamically balanced. The external converter shell is balanced independently of the converter stator and turbine to ensure the converter is accurately balanced.

100% installation of a NEW cooler bypass valve.

JASPER finishes all bushing and thrust surfaces to 15 RA or less. This prevents premature bushing and washer failure.

100% installation of NEW driven transfer gear bearing and race sets.



Comparison of the OE 4 plate friction design compared to JASPER's 5 plate design.

Torque capacity in both the 2-4 and overdrive clutches are increased by 25%. JASPER updates each of these clutches from their original 4 plate friction design to now include 5 friction plates.

100% installation of a NEW TCC solenoid and NEW lock-up lining on each 62TE.

JASPER installs a NEW heavy duty billet lock-up piston for the 2011-2017 3.6L FWD & AWD, and 2014-2018 3.6L Promaster.

Prior to installing the valve body, all clutches are hydraulically tested to detect leaks within each respective clutch circuit. This process helps reduce the likelihood of clutch failure.



100% NEW Billet Front Cover.

JASPER remanufactures each solenoid pack and each solenoid receives NEW seals. The solenoids are qualified using JASPER-designed test equipment that simulates vehicle operation. The range switch is also tested to ensure proper function.

All critical hydraulic sealing areas in the pump, valve body, and case are checked for flatness to ensure that hydraulic leaks do not cause premature failures.

Each JASPER Transmission undergoes dynamometer testing to ensure proper gear ratios, line pressure, cooler pressure, cooler flow, and noise.



3 Year /100,000 Mile Nationwide | Transferable Warranty Full warranty disclosure available at www.jasperengines.com or upon request. Specifications subject to change without notice.

800-827-7455 • WWW.JASPERENGINES.COM